

HyGold 60

Naphthenic Base Oil Marketing Specification

This severely hydrotreated naphthenic base oil is primarily used in the metalworking and compounder blending industries. It has a low pour point, a low odor level, excellent color, and resistance to discoloration by heat or ultraviolet light.

TEST DESCRIPTION	TEST METHOD	SPECIFICATIONS		TYPICAL VALUES
Physical Properties		MIN	MAX	
Viscosity, SUS at 100°F (37.8°C)	ASTM D2161	50.0	65.0	60.3
Viscosity, SUS at 210°F (98.9°C)	ASTM D2161			34.2
Viscosity, cSt at 40°C (104°F)	ASTM D445	7.0	12.0	9.6
Viscosity, cSt at 100°C (212°F)	ASTM D445		3.0	2.4
API Gravity, 60°F (15.6°C)	ASTM D1250			28.3
Specific Gravity, 60°F (15.6°C)	ASTM D4052			0.8854
Viscosity-Gravity Constant	ASTM D2501			0.856
Density, lbs/gal at 60°F	ASTM D1250			7.373
Density at 15.6°C, g/cm ³	ASTM D1250			0.8845
Molecular Weight	ASTM D2502			269
Flash Point, COC, °F (°C)	ASTM D92	295 (146)		310 (155)
Flash Point, PMCC, °F (°C)	ASTM D93	275 (135)		287 (142)
Color, ASTM	ASTM D6045		0.5	L0.5
Pour Point, °F (°C)	ASTM D5950		-45 (-43)	-80 (-62)
Water Content	ASTM D7546M	PASS		PASS
Appearance	ASTM D4176M	PASS		PASS
Chemical Properties				
Acid Number, mg KOH/g	ASTM D664		0.05	0.01
Aniline Point, °F (°C)	ASTM D611	160 (71)	180 (82)	170 (77)
Sulfur, ppm	ASTM D7212		500	34
Health and Safety Properties				
Polycyclic Aromatic Compounds, wt%	IP 346		3	<3
Modified Ames Assay, MI	ASTM E1687		1	<1
FDA Regulation	21 CFR 178.3620 (C)	PASS		PASS

HyGold 60 is a product of Ergon Refining, Inc.
February 9, 2024